

## **CARU Offshore Containers portfolio**

Closed top containers DNV 2.7-1/EN 12079 certified	LxWxH	Payload during offshore use
6ft mini	6'x 6'x 8'	5,000kgs
With removable shelf		
6ft mini	6'x 6'x 9'	5,000kgs
With removable shelf		
8ft dv	8' x 2200 x 2260mm	10,000kgs
10ft dv	10'x 8'x 8'6	11,040kgs
15ft dv	15'x 8'x8'6	
20ft dv	20'x 8'x 8'6	13,530kgs
20ft low roof	20'x 8'x 8'	13,530kgs
20ft HC	20'x 8'x 9'6	13,320kgs

Baskets and open top containers	LxWxH	Payload during offshore
DNV 2.7-1/EN 12079 certified		use
10ft HH open top with tarp	10'x 8'x 4'3	10,000kgs
10ft hard top OT	10'x 8'x 8'6	10,400kgs
With removable steel roof		
20ft HH open top with tarp	20'x 8'x 4'3	13,500kgs
20ft HH open top with tarp	20'x 8'x 4'3	21,000kgs
Heavy Duty		
20ft HH open top with tarp	20'x 8'x 4'3	13,500kgs
Vith side access		
Oft open top with tarp	20'x 8'x 8'6	13,250kgs
20ft hard top OT	20'x 8'x 8'6	12,320kgs
With removable steel roof		
39ft basket	39'x 4'x 4'	10,000Kgs
9ft basket with pipe support	39'x 4'x 4'	10,000kgs
53ft basket	53'x 4'x 4'	10,000kgs



Miscellaneous DNV 2.7-1/EN 12079 certified	LxWxH	Payload during offshore use
Boat shaped waste skip	3308x2002x	8,500kgs
	1500 <u>mm</u>	
Mud Skip	2202x1842x	9,300kgs
	1543 <u>mm</u>	

Refrigerated containers DNV 2.7-1/EN 12079 certified	LxWxH	Payload during offshore use		
10ft reefer.	10'x 8'x 4'3	7,820kgs		
Standard Thermo King equipment, but flexible with new				
units				

## **Other designs**

All other required types can be engineered to order. CARU has the inhouse engineering team and own surveyors on production side to facilitate this process.